

HYDRO50L - HIGH PURITY HYDROGEN GENERATOR MODULES



H₂

APPLICATIONS

- ✓ Combustion gas for FID Analyzers
- ✓ Carrier gas for Gas Chromatographs
- ✓ Protection gas

DESCRIPTION

PEUS-Instruments designed the **HYDRO50L** product line of **High Purity Hydrogen Generator** modules for FID and CARRIER GAS, to fit almost any type of application which needs High purity H₂ production close to the consumer in laboratory environment.

Based on the field proven Solid Polymer Electrolyte (PEM) cell technology, pure Hydrogen is produced at low pressure from electricity and high quality distilled water (ZEROWATER). This process can be started on demand and does not require any caustic solution.

The produced Hydrogen is available 24/7 with constant purity superior to **99.999%** at output flows of **100 to 600 Ncc/min** (depending on the model). The H₂ output pressure is regulated electronically and can be set from 0.5 to 7 bar.(7 to 102 psig).

Each instrument is equipped with high performance communication interfaces (RS485, Ethernet, WLAN) to create a very flexible gas network with local or central control.

Due to the softwares being focused on safety, automatic regulation and reliable communications, the **PEUS-Instruments HYDRO50L High Purity Hydrogen Generator** modules are easy to install, reliable, safe and pleasant to operate.

BENEFITS

- ✓ Reduces in operation costs. Return on investment within 2 years.
- ✓ Improves resolution and detection limit versus Helium only usage. Provides High pressure stability.
- ✓ H₂ available 24/7 at constant purity. No contamination.
- ✓ Independent source of Hydrogen that does not require any piping and can be easily moved around the laboratory. Remote control from PC, I-phone and I-pad
- ✓ Stackable casing for low footprint gas generator network assembly.
- ✓ Very safe operation, internal leak-test, automatic shut-down, over-pressure valve, current and voltage limits.
- ✓ No handling and storage of cumbersome gas cylinders. No cylinder rental fee.
- ✓ Extended autonomy with 5L water tank.





HIGH PURITY HYDROGEN GENERATOR MODULES

SPECIFICATIONS

Models	HYDRO50L-100, HYDRO50L-160, HYDRO50L-250, HYDRO50L-300, HYDRO50L-500 and HYDRO50L-600
H2 Outflow @ 1013/20°C	HYDRO50L-100 = 100 Nml/min ; HYDRO50L-160 = 160 Nml/min HYDRO50L-250 = 250 Nml/min ; HYDRO50L-300 = 300 Nml/min HYDRO50L-500 = 500 Nml/min ; HYDRO50L-600 = 600 Nml/min
H2 purity	>99.999% (maximum HC content: 0.1ppm)
Dew point	-40°C
Outlet Pressure	From 0.5 to 7 bar (7 to 102 psig), adjustable by software.
Water quality	PEUS-Instruments ZEROWATER: High purity distilled+filtered water. TOC free.
Water capacity	5L tank.
Water consumption	5L water generates about 6000L Hydrogen
Safety	Low H2 stored volume; over pressure valve; internal leak test; automatic shut down; maximum current limit, water quality, over temperature.
Manual control	ON-OFF power switch
Remote control, Communications	<ul style="list-style-type: none"> ■ By PEUS-Instruments Gas Network Controller, (communication by RS485), maximum distance to module : 100m ■ Through 2 potential free relay contacts (I/O), ■ RS485 (Mod-Bus), USB. ■ Trough Ethernet 10/100 network (option) ■ Trough WLAN network, with PC, I-Phone, I-Pad (option) ■ Log book download by USB.
H2 outlet fitting	Stainless steel 1/8" OD compression
Power supply	Automatic switching from 90VAC to 260VAC, 47 to 63 Hz
Power consumption (max at full flow)	HYDRO50L-100 to HYDRO50L-300: maximum 150W HYDRO50L-500 and HYDRO50L-600: maximum 300W
Dimensions	W=220mm/8.7ins, H=135mm/5.3ins, D=380mm/14.9ins , stackable
Net weight (Kg/lbs)	HYDRO50L-100 to HYDRO50L-300: 9 Kg / 20 Lbs HYDRO50L-500 and HYDRO50L-600 : 11Kg / 24Lbs
Certification	CE

ORDERING NUMBERS

Model	Article #
HYDRO50L-100	731101
HYDRO50L-160	731102
HYDRO50L-250	731103
WLAN Interface option	731181
ZERO WATER 3x5L refill	711091

Model	Article #
HYDRO50L-300	731104
HYDRO50L-500	731106
HYDRO50L-600	731107
Ethernet Interface option	731182
ZERO WATER 12x5L refill	711092

PEUS- INSTRUMENTS GmbH

Advanced engineering and reliable products from Germany

Max-Roth-Strasse 1
D – 76571 GAGGENAU, GERMANY
order@peus-instruments.com

Telephone: +49 7225 9636 3800
Telefax : +49 7225 9636 3899
www.peus-instruments.com